

Full-Scale Accelerated Pavement Tests Geogrid Stabilization of Thin Asphalt Pavements

Research Organization

US Army Corps of Engineers
Engineer Research and Development Center

Sections Tested

2 inches (51 mm) HMA over 8 inches (203 mm) base (control)
3 inches (76 mm) HMA over 8 inches (203 mm) base (control)
2 inches (51 mm) HMA over 8 inches (203 mm) base over TX140

Testing Conducted


Thickness Validation & Material Characterization
Instrumentation of sections
Pavement Characterization (post construction)
HVS-A Traffic testing, FWD analysis
Post trafficking forensics (in-field CBR, rutting of layers,...)





Key Findings

Control sections rutted quicker than the TX140 stabilized section.


Pavement life of the TX140 stabilized section delivered over 18 times the traffic of the control section.



Full-Scale Accelerated Pavement Tests Geogrid Stabilization of Thin Asphalt Pavements





Stabilized with TriAx




Report Item 1

Control Sections



Report Item 4



Report Item 5

Test Plan and Section Layout

- Rural Collector Road (15% trucks consistent with a Category III roadway)
- 20 year performance period
- Subgrade CBR 3%
- Change in serviceability of 2.2 – suggested by AASHTO for lower volume roadways

Full-Scale Accelerated Pavement Tests Geogrid Stabilization of Thin Asphalt Pavements

Tensar®




Significant procedures in place to reduce variability in testing (subgrade, base, asphalt, climatic impacts,...). APT testing is much more accurate than most field testing.



[Click above to go to:
https://www.youtube.com/watch?v=LIXcj9uqHIU](https://www.youtube.com/watch?v=LIXcj9uqHIU)

Instrumentation/Dynamic Sensors



Full-Scale Accelerated Pavement Tests Geogrid Stabilization of Thin Asphalt Pavements

Heavy Vehicle Simulator
(HVS-A). Capable of
applying loads between
10,000 and 100,000 lbs.

Uniformly distributed
traffic load with typical
wander introduced.






Falling Weight Deflectometer

- Tests performed pre-traffic, during trafficking and post trafficking
- Impulse Stiffness Modulus (ISM) values were calculated to determine if the base was stress weakening or hardening.

Full-Scale Accelerated Pavement Tests Geogrid Stabilization of Thin Asphalt Pavements

FWD Stiffness Values of the Section As Trafficking Accumulated




*“This is evidence that the geogrid reinforcement (TriAx TX140) **not only provided enhanced stiffness** to the aggregate base during construction, **it also maintained the stiffness of the aggregate base** throughout trafficking to the levels tested in this study. “*




Rutting

- Measured at 5 locations along each test item
- Measurements taken at selected trafficking intervals
- Rutting occurred quicker in the unstabilized sections.


Full-Scale Accelerated Pavement Tests Geogrid Stabilization of Thin Asphalt Pavements






Full-Scale Accelerated Pavement Tests Geogrid Stabilization of Thin Asphalt Pavements




833,333 Cars
161 Buses
90 Dump Trucks



4,166,667 Cars
803 Buses
451 Dump Trucks




37,500,000 Cars
7,229 Buses
4,056 Dump Trucks




With a Layer of Tensar® TriAx® Geogrid

Summary of Testing


- Tensor TriAx stabilized base can significantly improve the performance of a pavement by maintaining stiffness of a pavement section and reducing rutting at the surface.
- At rutting levels of 0.25-0.5 inches, sections stabilized with Tensor TriAx provided over 18 times that of the control, and over 7 times that of adding an extra inch of asphalt.



5,400 passes



12,640 passes



With a Layer of Tensor® TriAx® Geogrid

100,000+ passes